







- SPECIFICATION**
- 1. Rating : DC 12V 30V , 1.0A 3.0A
 - 2. Contact resistance : ≤30mΩ
 - 3. Insulation resistance : ≥100MΩ
 - 4. Withstand voltage : 500VAC
 - 5. Insertion and extraction force : 3-20N
 - 6. life test : 5,000 cycles

⑥	COVER	1	PF	
⑤	CONTACT FOOT	1	BRASS	Sn-Plating
④	PIN	1	BRASS	Ni-Plating
③	SPRING	1	PHOSPHOR BRONZE	Sn-Plating
②	FLAT PIECE	1	BRASS	Sn-Plating
①	HOUSING	1	PBT	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5 ±0.2


Above 5 ~ 15 ±0.3

Above 15 ~ 30 ±0.4

Above 30 ~ 50 ±0.5

Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L		TITLE	JACK
Ming Ming Zou	6/8/23				
CHECKED BY:	DATE	FINISH		MODLE	DC JACK
Ning Ning Su	6/8/23				
APPROVED BY:	DATE	SCALE	1 : 1	DWG NO.	GD-DC-0116X
Jia Xiang	6/8/23	SHEET NO.	1 of 1	PART NO.	
					SIZE
					A4
					VER
					R4

ITEM NO.	DESCRIPTION	DRAWN	DATE
4	更新材質	Jack	050420
3	更新尺寸	Jack	121119
2	更新尺寸標示位置	Jack	082719
1	更新尺寸	Jack	080519