












MODEL NO.	DC-097DH
SCHEMATIC	
CENTER PIN	$\phi 0.65\text{mm}$



*MATERIAL

- TERMINAL 1 :BRASS
TERMINAL 2 PHOSPHOR BRONZE
TERMINAL 3 :BRASS
HOUSING :PA6T




SPECIFICATION

- Rating : DC 16V 2.5A
- Contact resistance : $\leq 50\text{m}\Omega$
- Insulation resistance : $\geq 100\text{M}\Omega$
- Withstand voltage : 500VAC
- Insertion and extraction force : 3-30N
- life test : 5,000 cycles

P.C.B LAYOUT MOUNTING PATTERN (TOP VIEW)



东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :	Up to 5 ± 0.2 Above 5 ~ 15 ± 0.3 Above 15 ~ 30 ± 0.4 Above 30 ~ 50 ± 0.5 Angle $\pm 0.3^\circ$	3RD. ANGEL'S		UNITS	MM
-------------------------------------	--	--------------	---	-------	----

DRAWN BY:	DATE	MAT'L		TITLE	JACK
Jack Lu	08/12/14				
CHECKED BY:	DATE	FINISH		MODLE	DC JACK
Jacky Chen	08/12/14				
APPROVED BY:	DATE	SCALE	1 : 1	DWG NO.	DC-097DH-0.65
Tony Kao	08/12/14	SHEET NO.	1 of 1	PART NO.	DC-097DH-0.65
					SIZE A4
					VER R1

1	新增SPEC	Jack	081214
ITEM NO.	DESCRIPTION	DRAWN	DATE