








SCHEMATIC	1
	2
CENTER PIN	Ø2.0mm
	Ø2.5mm

线路板开孔尺寸图



SPECIFICATION


- 1.Rating : DC 12V 30V , 1.0A 3.0A
- 2.Contact resistance : $\leq 30m\Omega$
- 3.Insulation resistance : $\geq 100M\Omega$
- 4.Withstand voltage : 500VAC
- 5.Insertion and extraction force : 3-20N
- 6.life test : 5,000 cycles

⑥	COVER	1	PF	
⑤	CONTACT FOOT	1	BRASS	Sn-Plating
④	PIN	1	BRASS	Ni-Plating
③	SPRING	1	PHOSPHOR BRONZE	Sn-Plating
②	FLAT PIECE	1	BRASS	Sn-Plating
①	HOUSING	1	PBT	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :		Up to 5 ±0.2	3RD. ANGEL'S		UNITS	MM
		Above 5 ~ 15 ±0.3				
		Above 15 ~ 30 ±0.4				
		Above 30 ~ 50 ±0.5				
		Angle ±0.3°				

DRAWN BY:		DATE	MAT'L		TITLE	JACK	
Ming Ming Zou		6/8/23					
CHECKED BY:		DATE	FINISH		MODLE	DC JACK	
Ning Ning Su		6/8/23					
APPROVED BY:		DATE	SCALE	1 : 1	DWG NO.	GD-DC005-DX	SIZE
Jia Xiang		6/8/23					SHEET NO.
							R4