

PROPRIETARY INFORMATION
COMPANY CONFIDENTIAL

REV.	ECN. NO.	DESCRIPTION	ENG	DATE
A		INITIAL	Lucky	10/17/18

技术要求:

1. 电气及机械特性要求如下:

- 1.1 接触阻抗: 50mΩ以下;
- 1.2 绝缘阻抗: 100MΩ以上;
- 1.3 耐电压: 500V AC以上;
- 1.4 耐插拔: 5,000次以上;
- 1.5 插入力: 0.3~3.0kgf(3~30N);
- 1.6 拔出力: 0.3~3.0kgf(3~30N);

3D VIEW

01	CONTACT A	COPPER ALLOY	1 PCS
02	CONTACT B	COPPER ALLOY	1 PCS
03	CONTACT C	COPPER ALLOY	1 PCS
04	CONTACT E	COPPER ALLOY	1 PCS
05	CONTACT F	COPPER ALLOY	1 PCS
06	CONTACT G	COPPER ALLOY	1 PCS
07	CONTACT D	COPPER ALLOY	1 PCS
08	HOUSING	HIGH TEMPERATURE PLASTIC MATERIAL	1 PCS
09	COVER		1 PCS
10	INSULATOR		1 PCS
11	RING	COPPER ALLOY	1 PCS

03	PJ35B023-F06G1BA-C	铜套(喷砂180目+化学镀), 端子半全镀0.7, 主体黑色
02	PJ35B023-F06G1BA-B	不锈钢(喷砂180目+钝化), 端子半全镀0.7, 主体0.050绿色
01	PJ35B023-F06G1BA-A	铜套(喷砂180目+化学镀), 端子半全镀0.7, 主体白色

MEASURE POINT:
QUADRANT POINT
TANGENCY POINT
INTERSECTION POINTUNLESS OTHERWISE
SPECIFIED, TOLERANCE:
X. ±0.25
X.x ±0.20
X.xx ±0.15
X.xxx ±0.10
ANGULAR ±3°

东莞市高迪电子有限公司

DESIGN: Lucky
CHECKED
APPROVED
PART NO.
DRAWING NO.TITLE:
Ø3.5 四极圆形耳机线式正向
插嘴外径6.00mm
REV.: A
SCALE: 1:1
UNIT: mm
SIZE: A4
SHEET: 1/1