






CAD FILE:



注: "*"表示关键尺寸(6个)

P.C.B LAYOUT
BOTTOM VIEW

SCHEMATIC (SHORTING)

拨动开关立式技术参数:

1. 额定负荷: DC 30V 50V 0.3A 0.5A
2. 接触阻抗: $\leq 50\text{m}\Omega$
3. 绝缘阻抗: $\geq 100\text{m}\Omega$ DC500V
4. 耐焊温度: $250 \pm 5^\circ \text{C}$ 5s
5. 使用寿命: 10,000 cycles
6. 使用温度: -25°C to 80°C
7. 使用湿度: $\leq 85\% \text{ RH}$
8. 操作力: 160gf 256gf 300gf 可定制
9. 手柄长度: 2mm-10mm 可定制

NO.	PARTS	MATERIALS	Q'TY	FINISH	TOLERANCE UNLESS SPECIFIED	DATE	DESCRIPTIONS OF REVISION	APPD.
8								
7	STEEL BALL	STEEL	1	NATURAL				
6	SPRING	STEEL WIRE	1	NATURAL				
5	CONTACT CLIP	PBS STRIP	2	Ag PLATED				
4	TERMINAL	BRASS STRIP	8	Ag PLATED				
3	BASE	PHENOLIC RESIN	1	NATURAL				
2	FRAME	STEEL STRIP	1	Ni PLATED				
1	NOB	POM	1	BLACK				



东莞市高迪电子有限公司

WITHIN
OVERA
ISSUE2012-10-28
DATE

初版

DESCRIPTIONS OF REVISION

APPD.

TITLE : VERTICAL SLIDE SWITCH

UNIT : mm

DRWG NO.:

MODEL:

SCALE: 3:1

DWN.

2012-10-28

CHK'D

2012-10-28

APPD.