





Order data/订货信息

Contacts/芯数	Coding	Part number/料号	Qty	Contacts/芯数	Coding	Part number/料号	Qty
02Pin	A-code	M12A02-08-081	1000pcs				
03Pin	A-code	M12A03-08-081	1000pcs				
04Pin	A-code	M12A04-08-081	1000pcs				
05Pin	A-code	M12A05-08-081	1000pcs				
06Pin	A-code	M12A06-08-081	1000pcs				
07Pin	A-code	M12A07-08-081	1000pcs				
08Pin	A-code	M12A08-08-081	1000pcs				

Specifications/技术参数

Pin numbers/芯数	03Pin	04Pin	05Pin
Rated voltage/额定电压	50V/63V		
Rated current/额定电流	12A		
Standards/regulations/标准	IEC 61076-2-101		
Termination接线方式	Solder/焊线式		
Connector locking system/锁紧方式	Screw/螺锁		
Degree of protection/防护等级	IP67/IP68		
Wire gauge(mm ²)/线规(mm ²)	0.14mm ² ~0.75mm ²		
Wire gauge(AWG)/线号(AWG)	26AWG~18AWG		
Mechanical operation/插拔次数	100 mating cycles Min		
Ambient temperature (operation)/工作温度	-25℃~+85℃		
Contact resistance/接触电阻	≤5mΩ		
Insulation resistance/绝缘电阻	≥1000MΩ		
Connector body material/胶芯材料	PA66		
Pin material/端子材料	Brass with gold plated		
Screw material/螺丝材料	Brass with nickel plated		
Gasket material/胶圈材料	Fluorine ring/氟胶圈		

Pin assignment front view/针位分布前视图



 東莞市高迪電子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L		TITLE	CONNECTOR
Jack Lu	12/13/19	FINISH		MODLE	M12XXX- -08-081
CHECKED BY:	DATE	SCALE	1 : 1	DWG NO.	
Jacky Chen	12/13/19	SHEET NO.	1 of 1	PART NO.	
APPROVED BY:	DATE				
Tony Kao	12/13/19				