





项目		尺寸(mm)									面板开孔尺寸(mm)		
系列	型号	A	B	E	M	P	N	L	S1	e	Ws	Ø	种类
0K	Z3	18	18	2.5	3.5	7	16.0	22.5	12.5	M14*1.0	12.6	14.1	A
1K	Z3	20	20	5.5	3.0	10	21.5	30.0	14.5	M16*1.0	14.6	16.1	A
2K	Z3	25	25	5.0	3.5	10	22.0	29.0	18.5	M20*1.0	18.6	20.1	A
3K	Z3	30	31	7.0	4.5	12	29.0	37.5	22.5	M24*1.0	22.6	24.1	A

产品主要技术参数

特性	参数
锁紧方式	推拉自锁
工作温度	-55°C~+125°C
最大潮湿	在60°C/140°F时最高达到95%
屏蔽性能	75dB(10MHz) 40dB(1GHz)
抗振动性能	15g[10Hz~2000Hz]

特性	参数
盐雾试验	96hr
抗冲击性能	100g,6ms
机械寿命	5000次
防护等级	IP68




東莞市高迪電子有限公司

DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L		TITLE	CONNECTOR
Jack Lu	12/13/19			MODLE	Z3插座-B
CHECKED BY:	DATE	FINISH		DWG NO.	
Jacky Chen	12/13/19	SCALE	1 : 1	PART NO.	
APPROVED BY:	DATE	SHEET NO.	1 of 1		
Tony Kao	12/13/19				

SIZE

A4

VER

R1