






板后安装针型插座(卡扣式)
E13 Male Back Mount Solder Receptacle(Bayonet)

E13B - P 3B - PWF


芯数:
A:2 3 4 5 6 7 8 9
10 12 14 18
B:2B 3B 4B
C:8C



产品参数 PRODUCT PARAMETERS

外壳材料 Shell material	热塑性塑料PA66 阻燃等级: V-0 Thermoplastic plastic PA66, flame retardant grade: V-0	绝缘电阻 Insulation resistance	2000 mΩ
插针材料 Contact material	铜镀金 Copper gold-plated	适用温度 Applicable temperature	-40℃ ~ +105℃
连接方式 Coupling	螺纹锁紧(T);卡扣锁紧(B) Thread (T); Bayonet(B)	电缆线径 Cable diameter	6.0mm~10.0mm
接线方式 Termination way	焊接 Solder	防水等级 Waterproof grade	IP67、IP68
插拔次数 Durability	≥500次(Cycles)		

 东莞市高迪电子有限公司
DONG GUAN GAO DI ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED:	Up to 5 Above 5 ~ 15 Above 15 ~ 30 Above 30 ~ 50 Angle	±0.2 ±0.3 ±0.4 ±0.5 ±0.3°	3RD. ANGEL'S		UNITS	MM
------------------------------------	--	---------------------------------------	-----------------	---	-------	----

DRAWN BY:	DATE	MATL		TITLE	CONNECTOR
Jack Lu	12/13/19	FINISH		MODLE	E13B - P 3B - PWF
CHECKED BY:	DATE	SCALE	1 : 1	DWG NO.	
Jacky Chen	12/13/19	SHEET NO.	1 of 1	PART NO.	
APPROVED BY:	DATE				
Tony Kao	12/13/19				