







PCB LAYOYT



C5	—○—○—	Defect	Inserted Card
C5	—○—○—	Defect	Withdrawal Card(Normal)

Pin Assignments

PIN	Name
C1	Vcc
C2	RST
C3	CLK
C4	Reserved
C5	GND
C6	Vpp
C7	I/O
C8	Reserved

SPECIFICATION

Electrical :

- 1.Current Rating: 1.0A
- 2.Contact Resistance: 100 mΩ Max.
- 4.Insulation Resistance: 1000 MΩ Min.

Environmental:

- 1.Operating Temperature: -25℃ ~ +85℃.

Material:

- 1.Housing: LCP
- 2.Contact: Copper Alloy
- 3.Shell: Stainless Steel

Finish:

- 1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall
- 2.Shell: Nickel under Plated surface layer



TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	09/17/18			
CHECKED BY:	DATE	FINISH	MODLE	MICRO SIM H1.24
Jacky Chen	09/17/18			
APPROVED BY:	DATE	SCALE	DWG NO.	MSIM-0124-S267
Tony Kao	09/17/18	1 : 1		
		SHEET NO.	PART NO.	MSIM-0124-S267

SIZE
A4
VER
R